

ZERO.6

DAFA foil adhesive

DAFA foil adhesive is a part of DAFA AirStop System and is used for the airtight bonding of vapour and moisture barriers.

DAFA foil adhesive is a water-based dispersion adhesive for the airtight bonding of vapour and moisture barriers in accordance with DIN 4108.

Areas of application

DAFA foil adhesive is used for airtight bonding in connection with moisture barriers and vapour barriers in accordance with DIN 4108 in the climate barrier of buildings. The product is free from solvents and can be used without moulded strips due to its excellent adhesive properties. DAFA foil adhesive smoothes out irregularities, moves with the building and is also long-lasting.

DAFA foil adhesive is used for creating airtight adhesive joints with moisture and vapour barriers on absorbent surfaces such as plaster, concrete or untreated wood.

Product information

- Elastoplast adhesive with liquid dispersion and ester gum for vapour / moisture barriers
- Solvent-free
- Strong and long-lasting adhesive properties
- Stable
- Smoothes out irregularities
- Long-lasting adhesive properties
- Durable
- Moves with the building
- Does not require moulded strips
- The product has been tested by the Danish Technological Institute as the strongest adhesive on the Danish market

Important instructions

The surface must be firm, dry and free of oil and grease. Important: The substrate must be absorbent, e.g. plaster, cement or untreated wood.

The adhesive must be applied in strips at least 8 mm wide. Immediately afterwards, carefully fix the vapour / moisture barrier onto the wet adhesive strip (do not press flat, as the strip must be at least 4 mm thick), remember strain-relief folds – or press the vapour / moisture barrier firmly onto the dry adhesive strip.

Start by testing the procedure.

Recommended installation temperature: +5°C to +35°C

Protect against frost.

Durability: See best before date on the tube.

Read more at www.dafa-as.com



In alliance with  Insurance Solutions



DAFA foil adhesive.



DAFA foil adhesive in 580 ml alu foil bag and 310 ml tube.

Technical specifications	
Consistency	Paste
Hardening time	15 - 20 mins at 23 °C, 50 % RH.
Temperature resistance	-20 °C to +80 °C
Installation temperature	+5 °C to +35 °C
Storage	Store in a dry place between 5 °C and 30 °C
Colour	Light blue

Dimension	Contents per box / roll	DAFA item no.	EAN no.
Foil adhesive 310 ml tube	20 pcs per box	620014510	5705636344560
Foil adhesive 580 ml bag	20 pcs per box	620014511	5705636344577